



optional EQUIPMENT VERSIONS

- » hydraulically driven side brush for sweeping close to the edge (with water spray unit, if required)
 - » Water-spray system for dust binding including water pump with or without water tank (100 l or 200 l)
 - » Extra sturdy wheels we recommend for heavy-duty application.
 - » Flow control valve for infinitely variable speed control with pressure relief valve (> 90 l)
 - » Limiting lights (LED) acc. to StVZO (road traffic licensing authority) when driving in road traffic
 - » Signal flag holder und signal flags
 - » Special paint according to RAL (standard RAL 2004)
- » MACHINE-OWN HYDRAULIC SYSTEM with oil tank



The IDEAL 650 front sweeper is specially designed for use in industry and on construction sites. The sweeper is driven by an inside-mounted powerful hydraulic motor with twin pressure relieving valve.

The brush made of 100 % PP mixed bristles trim can be ideally used indoor as well as outdoor. Here, in particular, the bristles are V-shaped to sweep up both solidified dirt and fine dust. The oscillating suspended brush adapts optimally to the ground and provides good dust encapsulation. This sweeper is ideally suited for cleaning halls and buildings.

In addition, the sweeper is equipped with an integrated hydraulically dischargeable collecting tank with high-filling flap and a dust cover.

INSTALLATION VARIANTS

- » Fork-tines attachment

COMBI ATTACHMENT consisting of:

- » Fork-tines attachment & wheel loader attachment
- » Fork-tines attachment & three-point linkage



TECHNICAL DATA

	130 cm	150 cm	180 cm	210 cm
Working width (straight) [cm]	130	150	180	210
Total width [cm]	155	175	205	235
Weight including collecting container [kg]	455	497	516	556
Volume collecting container [l]	210	240	290	335
required oil flow rate (at 160 bar) [l]	25	25	25	30

