

# TUCHEL-SNOW

VARIO



The VARIO snow plough can be mounted on almost any carrier vehicle and impresses with its flexibility.

The robust carrier frame with two hydraulically adjustable folding wings can be used separately in V, Y or straight position. The non-icing spring flap segments serve as overrun protection with overload protection via a nitrogen accumulator.

In addition, steplessly height-adjustable castors and the left and right edge deflectors, which protect the blade from damage, are included in the basic equipment. As option, the blade can be purchased with a torsion-resistant PU-lip, steel trim or a highly abrasion-resistant municipal scraper bar.

## INSTALLATION VARIANTS

- » A-frame
- » Three-point linkage
- » Wheel loader / telescopic attachment
- » Municipal vehicle attachment (up to 180 cm)
- » Attachment plate fitting to Unimog vehicles DIN 76060 (from 210 cm)
- » Fork-tines attachment

## optional EQUIPMENT VERSIONS

- » Perfect control for wing adjustment in straight position right/left or from Y-shape to V-shape in one operation
- » Side levelling for optimum ground adjustment
- » Extra sturdy wheels for heavy-duty application.
- » Skids instead of castor rollers
- » Limiting lights (LED) acc. to StVZO (road traffic licensing authority) when driving in road traffic
- » Signal flag holder und signal flags
- » Special paint according to RAL (standard RAL 2004)



## TECHNICAL DATA

	150 cm	180 cm	210 cm	240 cm	260 cm	320 cm	370 cm
Clearing width (straight/angled) [cm]	150/135	179/161	218/196	238/214	268/224	318/265	368/300
Clearing (V-shape / Y-shape) [cm]	135/135	161/160	199/193	217/211	226/222	273/257	281/320
Weight (without attachment) [kg]	187	210	318	335	421	468	550
Height [mm]	570	570	770	770	770	770	825
Angled position (rear/front)	28 °/27 °	28 °/27 °	26 °/28 °	26 °/28 °	34 °/34 °	32 °/36 °	41 °/30 °

# SNOW

# VARIO

