



The Tichel-Trac Trio is the appropriate carrier vehicle for minimising heavy physical work in agriculture, landscaping, municipalities or in the construction industry. Due to the compact design you have everything in view from the driver's seat and short distances when changing tools.

The four-wheel drive, the rear steering axle and the hydraulic steering distinguish this tricycle. You can use the Tichel-Trac Trio perfectly in difficult terrain and in the tightest of spaces.

Two double-acting control circuits ensure rapid and powerful working. The joysticks of the working hydraulics are within easy reach, right next to the adjustable seat.

The completely swivelling plastic bonnet makes the components easily accessible for maintenance and service. With the Tichel-Trac Trio you have a powerful vehicle that is easy to operate.

### optional EQUIPMENT VERSIONS

- » Bedding device "E" with agitator shaft & tipping device, volume 450 l, manure pusher 145 cm, side brush Ø 850 cm (100% PP)
- » Bedding device "F" with screw conveyor, volume 160 l, manure pusher 145 cm, side broom Ø 850 cm (100% PP)
- » Feed auger 110 cm (option: concentrated feed distributor)
- » Hydraulic manure slider 130 cm with double lip (Option: side sweeping broom)
- » Rubber slider 160 cm hydraulic right/left swivelling
- » Sweeper Simplex 120 cm
- » Snow blade L-SK 125 cm
- » Radial broom Ø 1200 cm, 100 % PP, hydr. driven, with right/left rotation
- » Radial broom with feed guide plate
- » Weed brush Ø 750 cm hydraulic right/left swivel device hydraulic 4-fold multi coupling



### TECHNICAL DATA

	2 cylinders	3 cylinders
Engine [kW (PS)]	10.3 (14) at 3,200 rpm	14.9 (20) at 3,600 rpm
Hydraulic flow rate [l/min]	25 at 3,200 rpm	25 at 3,200 rpm
Tank capacity (hydraulic) [l]	65	65
Total width / turning circle (outside) [mm]	920 / 2.920 (3.660)	920 / 2.920 (3.660)
Weight [kg]	642 (ready for operation)	680 (ready for operation)

# TRAC

# TRIO