



Small, compact, agile and speedy - that's our new MINI 3. We have equipped the Tricycle with hydrostatic front-wheel drive for you as standard. Thanks to the rear steering axle the MINI 3 features a turning radius of only 490 mm. Due to the quick hitch the assembly and disassembly of many attachments are very user-friendly for you. In such a way, many activities around your farm can be done easily and quickly.

optional EQUIPMENT VERSIONS

- » Slurry scraper 105 cm, V-shaped, double lip with low-wear PU-lips
- » Slurry scraper with side brush \varnothing 600 mm, 100 % PP, hydraulic swivel, mechanical height adjustment
- » Bedding unit volume 48 l, for light-weight spreading material
- » Feed pusher / snow clearing blade 135 cm, right/left swivel-mounted, with low-wear scraper edge for optimum feed resupply, cleaning of the feed table and snow clearing
- » Feed blade / snow blade with hydraulic angling
- » Radial brush 105 cm, 100 % PP, hydraulically driven, two-way rotation
- » Radial brush with feed supply plate
- » Weed brush \varnothing 750 mm, mechanically adjustable
- » Sweeper 100 cm, brushes- \varnothing 320 mm, Swivel castors \varnothing 140 mm, inside-mounted hydraulic motor, including splash guard for free-sweeping version, levelling
- » High-tipping bucket, width 87 cm, volume 50 l, hydraulically operated tipping out



TECHNICAL DATA

MINI 3

Dimensions without attachment [mm]	W: 850 L: 1,690 H: 1.750
Engine / power	Honda GXV 390 / 7.6 kW (10.2 hp) / E-starter and reversing starter Loncin LC1P85FA / 7.4 kW (10 hp) / E-starter without reversing starter
Drive	hydrostatic front wheel drive through V-belt
Lifting system	hydraulic
Hydraulic connectors	1 x double-acting (12/11 l / 170 bar)
Weight basic vehicle [kg]	290 / 280
Turning radius [mm]	980