



A stable lever steering system and the big agrarian traction tyres ensure that the power rate is fully utilised. The basic unit is equipped as standard with a hydraulic drive and hydraulic connectors for other attachments. These can be mounted and dismantled without tools.

optional EQUIPMENT VERSIONS

- » **Slurry scraper** V-shaped, 100 cm, designed as a double-lip scraper, including levelling, galvanised, with low-wear Diepothan edges ensures easy and rapid cleaning of slotted floors even in the smallest of spaces
- » **Feed supply blade** 110 cm, can be swivelled to the right and left, including level compensation, powder-coated, with wear-resistant scraper edge for optimal resupply of the feed and simultaneous cleaning of the feed table
- » **Snow blade** 95 cm/height 40 cm, swivelling right and left with wear-resistant scraper edge, incl. level compensation, powder-coated
- » **Axial sweeper** 75 cm and 100 cm, hydraulically driven, brush diameter 320 mm, 100 % PP, powder-coated, swivelling right and left, incl. levelling
- » **Collecting container** 75 cm und 100 cm, powder-coated, matching to the axial sweeper, with scrape rail
- » **Radial brush** 80 cm, 100 % PP, powder-coated, hydraulically driven, two-way rotation
- » **Bedding unit** EL 48 litres volume, for light-weight spreading material



TECHNICAL DATA

	Farm-Clean
Dimensions without attachment [mm]	W: 610 L: 1,090 H: 1,040
Engine / power	Honda GCV 160 / 3.3 kW (4.5 hp)
Drive	hydrostatic, forward/reverse
Speed stages	1 (optionally stepless)
Hydraulic connectors	1 x double acting